



LCD15DMI-5I

desktop indoor standard slimline



Technische Daten

Display

LCD-Panel	15" TFT LCD
Auflösung	1024 x 768 (XGA)
Farben	16.2 Millionen
Helligkeit	500 cd/m² (typ.)
Sichtwinkel	176° H, 176° V (typ.)

Umgebung

Betriebstemperatur	0°C bis 45°C
Lagertemperatur	-20°C bis +60°C
Schutzart	IP65 frontseitig, IP21 rückseitig

Mechanik

Gehäuse	Aluminium, Pulverlack beschichtet
Farben	RAL 9005, 9006, 7035
Schutzglas	Stärke 3 mm, entspiegelt
Montage	Standbügel

LCD-Controller

Schnittstellen	DisplayPort™ 2x HDMI® VGA (15pol HD-SUB)
Menü Einstellung	Backlight, Helligkeit, Kontrast, Phase, Bildgröße, Auto Adjust, etc.

Stromversorgung

12V, 24V, 48V DC

Optionen

Farben	RAL-Farben
Schutzglas	ESG, Vinyl, Polycarbonat
Montage	Sonderbefestigung an Rückwand
Schnittstellen	zus. DisplayPort™, HDMI®, DVI Composite-Video, S-Video PAL/NTSC, SDI

Weitere Optionen auf Anfrage...

The Adopted Trademarks HDMI®, High-Definition Multimedia Interface, and the HDMI® Logo are trademarks or registered trademarks of HDMI® Licensing Administrator, Inc. DisplayPort™ and the Display-Port™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. HDBaseT™ is a trademark of the HDBaseT Alliance.

